

(12) **United States Patent**
Chen et al.

(10) **Patent No.:** **US 10,984,600 B2**
(45) **Date of Patent:** **Apr. 20, 2021**

(54) **APPARATUS, METHOD, AND SYSTEM FOR PRESENTATION OF MULTIMEDIA CONTENT INCLUDING AUGMENTED REALITY CONTENT**

3/0482 (2013.01); G06Q 50/28 (2013.01);
G06T 2207/10016 (2013.01); G06T
2207/30204 (2013.01)

(58) **Field of Classification Search**

None

See application file for complete search history.

(71) Applicant: **TIFF'S TREATS HOLDINGS, INC.**,
Austin, TX (US)

(72) Inventors: **Leon Chen**, Austin, TX (US); **Brian
Keffner**, Austin, TX (US); **Jocelyn
Seevers**, Austin, TX (US)

(73) Assignee: **TIFF'S TREATS HOLDINGS, INC.**,
Austin, TX (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

(21) Appl. No.: **16/403,975**

(22) Filed: **May 6, 2019**

(65) **Prior Publication Data**

US 2019/0362554 A1 Nov. 28, 2019

Related U.S. Application Data

(60) Provisional application No. 62/676,748, filed on May
25, 2018.

(51) **Int. Cl.**

G06T 19/00 (2011.01)

G06T 7/70 (2017.01)

G06T 7/20 (2017.01)

G06K 9/00 (2006.01)

G06Q 50/28 (2012.01)

(Continued)

(52) **U.S. Cl.**

CPC **G06T 19/006** (2013.01); **G06K 9/00671**
(2013.01); **G06T 7/20** (2013.01); **G06T 7/70**
(2017.01); **H04M 1/72555** (2013.01); **G06F**

References Cited

U.S. PATENT DOCUMENTS

8,040,361 B2 10/2011 Bachelder et al.

8,315,432 B2 11/2012 Lefevre et al.

(Continued)

OTHER PUBLICATIONS

H. Kawakita and T. Nakagawa, "Augmented TV: An augmented
reality system for TV programs beyond the TV screen," 2014
International Conference on Multimedia Computing and Systems
(ICMCS), Marrakech, 2014, pp. 955-960, doi: 10.1109/ICMCS.
2014.6911158. (Year: 2014).*

(Continued)

Primary Examiner — Peter Hoang


(74) *Attorney, Agent, or Firm* — Norton Rose Fulbright
US LLP

(57)

ABSTRACT

The present disclosure relates to methods, devices, and
systems for presentation of multimedia content. In an aspect
of the present disclosure, a method includes receiving, at a
processor of a mobile device, a plurality of images from a
camera, at least one image of the plurality of images
including an object. The method also includes displaying a
camera video stream based on the plurality of images,
displaying three dimensional (3D) augmented reality content
in the camera video content, and displaying video
content based on the 3D augmented reality content. The
video content is associated with the object.

24 Claims, 14 Drawing Sheets



(51)	Int. Cl. G06F 3/0482 H04M 1/725	(2013.01) (2021.01)	2013/0076790 A1	3/2013	Lefevre et al.	
			2013/0088514 A1	4/2013	Breuss-Schneeweis et al.	
			2013/0106910 A1	5/2013	Sacco	
			2013/0222371 A1	8/2013	Reitan	
(56)	References Cited	U.S. PATENT DOCUMENTS	2013/0249947 A1	9/2013	Reitan	
			2013/0303285 A1	11/2013	Kochi et al.	
			2013/0307855 A1	11/2013	Lamb et al.	
			2013/0321390 A1	12/2013	Latta et al.	
			2014/0028712 A1	1/2014	Keating et al.	
			2014/0078174 A1	3/2014	Williams et al.	
			2014/0108136 A1 *	4/2014	Zhao	G06Q 10/0833 705/14.49
			2014/0204119 A1	7/2014	Malamud et al.	
			2014/0225978 A1	8/2014	Saban et al.	
			2014/0228118 A1	8/2014	Hardy et al.	
			2014/0248950 A1	9/2014	Tosas Bautista	
			2014/0253590 A1	9/2014	Needham	
			2014/0282220 A1	9/2014	Wantland	
			2014/0306866 A1	10/2014	Miller et al.	
			2015/0032766 A1	1/2015	Greenbaum	
			2015/0062120 A1	3/2015	Reisner-Kollmann et al.	
			2015/0084951 A1	3/2015	Boivin et al.	
			2015/0154799 A1	6/2015	Rios et al.	
			2015/0206349 A1	7/2015	Rosenthal et al.	
			2015/0235423 A1	8/2015	Tobita	
			2015/0248785 A1	9/2015	Holmquist	
			2015/0301592 A1	10/2015	Miller	
			2015/0316985 A1	11/2015	Levesque et al.	
			2015/0332512 A1	11/2015	Siddiqui et al.	
			2015/0348329 A1	12/2015	Carre et al.	
			2015/0379770 A1	12/2015	Haley, Jr. et al.	
			2016/0012644 A1	1/2016	Lam	
			2016/0055677 A1	2/2016	Kuffner	
			2016/0093106 A1	3/2016	Black	
			2016/0098863 A1	4/2016	Liu et al.	
			2016/0104452 A1	4/2016	Guan et al.	
			2016/0217616 A1	7/2016	Kraver	
			2016/0217617 A1	7/2016	Barribeau	
			2016/0232713 A1	8/2016	Lee	
			2016/0232715 A1	8/2016	Lee	
			2016/0247320 A1	8/2016	Yuen et al.	
			2016/0247324 A1	8/2016	Mullins et al.	
			2016/0275722 A1	9/2016	Bretschneider et al.	
			2016/0307374 A1	10/2016	Kurz et al.	
			2016/0330161 A1 *	11/2016	Chakravarthy	H04L 51/30
			2016/0343168 A1	11/2016	Mullins et al.	
			2017/0053449 A1	2/2017	Lee et al.	
			2017/0084082 A1 *	3/2017	McTaggart	H04L 67/18
			2017/0116667 A1 *	4/2017	High	G06K 9/00671
			2017/0131964 A1	5/2017	Baek et al.	
			2017/0132842 A1	5/2017	Morrison	
			2017/0144068 A1	5/2017	Cohen	
			2017/0169598 A1	6/2017	York et al.	
			2017/0169614 A1	6/2017	Tommy et al.	
			2017/0216728 A1	8/2017	Logan et al.	
			2017/0221265 A1	8/2017	Lin	
			2017/0263056 A1	9/2017	Leppanen et al.	
			2017/0269712 A1	9/2017	Forsblom et al.	
			2017/0270698 A1	9/2017	Goslin	
			2017/0287225 A1	10/2017	Powderly et al.	
			2017/0337744 A1	11/2017	Martin	
			2017/0337747 A1	11/2017	Hull	
			2017/0337750 A1	11/2017	McKenzie et al.	
			2017/0351909 A1	12/2017	Kachler	
			2017/0352187 A1	12/2017	Haines	
			2018/0005435 A1	1/2018	Anderson et al.	
			2018/0012411 A1	1/2018	Richey et al.	
			2018/0024363 A1	1/2018	Wong et al.	
			2018/0040161 A1	2/2018	Tierney et al.	
			2018/0045963 A1	2/2018	Hoover et al.	
			2018/0075591 A1	3/2018	Du et al.	
			2019/0371073 A1 *	12/2019	Harviainen	G06F 3/011
OTHER PUBLICATIONS						
International Search Report and Written Opinion Issued in Corresponding PCT Application No. PCT/US2019/032583, dated Sep. 17, 2019.						

(56)

References Cited

OTHER PUBLICATIONS

International Search Report and Written Opinion Issued in Corresponding PCT Application No. PCT/US2019/032576, dated Nov. 12, 2019.

Breen et al., "Interactive Occlusion and Collision of Real and Virtual Objects in Augmented Reality" *European Computer-Industry Research Centre* 1995, 23 pages.

* cited by examiner




FIG. 1

200

210

ORDER FORM

220

240

222 SENDER: 242

224 ITEM(S): 244

226 RECIPIENT: 246

228 CONTACT : 248

230 ADDRESS: 250

232 AR CONTENT: 252

234 VIDEO CONTENT: 254

236 MESSAGE: 256

238 ACCESS CODE: 258

FIG. 2

Order data 140

Entry 142

Order No. 310	Item(s) ID 312	Sender Info 314	Recipient Info 316
AR Content ID 318	Video Content ID 320	Message ID 322	Identifier 324

FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9A





FIG. 9B




FIG. 9C




FIG. 10







FIG. 11

**FIG. 12**

**FIG. 13**

**FIG. 14**

1

APPARATUS, METHOD, AND SYSTEM FOR PRESENTATION OF MULTIMEDIA CONTENT INCLUDING AUGMENTED REALITY CONTENT

CROSS-REFERENCE TO RELATED APPLICATIONS

The present application claims benefit of U.S. Provisional Application No. 62/676,748 filed May 25, 2018, which is incorporated by reference herein in its entirety.

TECHNICAL FIELD

The present disclosure generally relates to a multimedia content delivery and presentation, and, but not by way of limitation, to methods, devices, and systems for delivering or presenting multimedia content including augmented reality content and video content in a camera video stream.

BACKGROUND OF THE INVENTION

With the proliferation of electronic devices, augmented reality (AR) has been implemented in a variety of contexts. Conventional implementations of augmented reality (AR) include a live direct or indirect view of a physical, real-world environment with elements that are augmented by computer-generated content, such as a graphic (e.g., an animation) and audio.

AR functionality is typically implemented using marker-less tracking or marker-based tracking. An example of marker-less based tracking is described in U.S. Pat. No. 8,797,353 in which an augmented reality (AR) feature is coupled with a physical object and marker-less tracking is used to present the AR feature on the physical object. For example, a first user captures an image of the physical object, attaches AR content to a location on the physical object represented in the image and sends a rich media message (associated with the AR content attached to the image) to a second user, and transfers the physical object to the second user. In some implementations, the first user may also attach a file, such as a text file (e.g., a text message), music file, or other personal message file. Using an AR viewer and the rich media message, the second user can view the physical object and see the AR feature appearing on the physical object. Such distribution of AR content in this manner is not without several limitations that impact use of the AR feature. To illustrate, the first user is required to capture an image of the first object, the first user has to know or have the ability to send the rich media message to the second user, and the marker-less tracking is often unreliable, thereby disrupting presentation of the AR feature.

In marker-based AR, an application (e.g., an AR viewer) is configured to recognize markers present in a real-world environment. In such implementations, the application must be programmed to recognize the markers, such as geospatial markers, 2D markers, or 3D markers. The AR viewer may detect the marker and launch the AR content based on recognition of the marker. In such systems, a device that includes the AR content is often required to store information for multiple markers and/or a large amounts of data corresponding to AR content for each marker.

Presenting AR content, such as 3D AR content in a live video stream can be challenging because 3D content often requires multiple models or point clouds, complex localization and mapping function, and is very data and computation intensive. AR systems are still in their infancy due the

2

technical complexities of implementing such systems. As AR content continues to grow in popularity and use, many challenging aspect of AR functionality will need to be identified and overcome to produce faster and more efficient AR systems.

SUMMARY

The present disclosure describes devices, systems, methods, and computer-readable storage media for providing augmented reality content in a camera video stream. For example, a mobile device having a camera and a display may display a live video stream captured by the camera and modify the live video stream with augmented reality content and pre-recorded video content that corresponds to an object, such as a packaged delivered to a user.

In some implementations, devices, systems, methods, and computer-readable storage media of the present disclosure enable requester of an order (for delivery of an object to a recipient) to request a multimedia message to be made available. The multimedia message may include augmented reality (AR) content that is provided in a live video stream at a device associated with the recipient. In addition, the requester (other entity) may provide video content to be included in the multimedia message such that the video content is presented along with the AR content—e.g., the video content may be present with and included in 3D AR content. To illustrate, video content may be assigned or attached to an order of an item to be delivered to a recipient. For example, the item may be included in a package having a marker and the package may be delivered to the recipient. Additionally, an identifier that corresponds to the video content and that is associated with the package is provided to the recipient.

In some implementations, the recipient of the package may utilize a mobile device to scan the identifier and send corresponding identifier data to a server associated with the order. Responsive to the identifier data, the mobile device may receive one or more content items, such as the video content, AR content (or an indication of selected AR content), text content, and/or image content. The mobile device (e.g., a processor) may initiate an AR viewer that causes the mobile device to provide at least one live video stream associated with a camera of the mobile device. The mobile device may display a target to direct a user to position the mobile device in a predetermined location with respect to a marker coupled to the package. By providing the target (e.g., a template) for the marker, a user is able to position the mobile device in an initial position, orientation, and distance with respect to the marker. In response to detection of the marker, the mobile device may establish a coordinate system with respect to the marker and initiate a multimedia message in which the AR content (e.g., 3D AR content) and the video content is included in the live video stream from the camera.

In some implementations, the mobile device includes presentation data associated with a location (e.g., 3D position information) of the video content within the 3D AR content. The presentation data may have an initial value that is calibrated to the coordinate system established based on detection of the marker. After detection of the marker, the mobile device may track one or more characteristics of the marker to determine a change in position (e.g., distance, rotation, translation) of the mobile device with respect to changes in features of the marker (e.g., size, angle, horizontal and/or vertical position within the display). The mobile device may modify the position data based on the determined change in position of the marker and/or the mobile

device. In some implementations, the mobile device may also generate a set of predicted presentation data values and select one of the predicted set of values for presentation of the video content. The selected value may be determined based on one or more inputs, such as motion data from a sensor (e.g., an inertial sensor) of the mobile device.

Thus, present disclosure describes systems, devices, and methods for providing multimedia content that corresponds to an object, such as a package, delivered to the recipient. In such implementations, a sender/requestor of the order is not required to have access to the package prior to delivery of the package to the recipient. The mobile device associated with the recipient is configured to implement a set rules, such as an AR viewer application, that provided one or more conditions for establishing a coordinate system with respect to the package and/or for dynamically determining video content placement data based on the coordinate system. To illustrate, the video content data may be determined as a function of marker characteristics and a movement prediction algorithm. Based on the video content placement data, the set of rules are further configured to determine and implement video content presentation characteristics (e.g., orientation, translation, size, scale, perspective, etc.) to dynamically adjust the video content for presentation. Accordingly, the video content may be efficiently presented with a live video stream such that the video content interacts with the AR content included in the live video stream. The displayed video content may further be presented based on movement and placement of at least a portion of the AR content such that occlusion and collision algorithm further coordinate and/or synchronize movement of the mobile device with presentation of the AR content and the video content within the live video stream. Thus, the present disclosure advantageously provides multimedia content by establishing a coordinate system in a controlled manner such that the one or more rules may be efficiently applied to dynamically determine adjustments/updates to presentation data associated with the video content and to select the presentation data based at least on features of marker and/or movement or predicted movement of a mobile device.

In an aspect of the present disclosure, one or more methods comprise: receiving, at a processor of a mobile device, a plurality of images from a camera, at least one image of the plurality of images including an object; displaying a camera video stream based on the plurality of images; displaying three dimensional (3D) augmented reality content in the camera video stream; and displaying video content based on the 3D augmented reality content, the video content associated with the object. In some such methods, the object includes a package having one or more items, the package delivered to a user associated with the mobile device, and presentation of the camera video stream including the 3D augmented reality content and the video content is associated with a multimedia message.

In some of the foregoing implementations, the one or more methods may comprise: receiving, at the mobile device, an application; storing the application at a memory of the mobile device; and accessing the application. Additionally, or alternatively, the one or more methods may comprise: receiving, at the processor, a first image from the camera, the first image including an identifier associated with the object; detecting the identifier included in the image; and sending, from the mobile device to a server, at least a portion of the image including the identifier or identifier data based on the identifier.

In some of the foregoing implementations, the one or more methods comprise: receiving, at the mobile device

from the server, the video content, where the video content corresponds to the identifier and is associated with a sender of the object, and where the video content comprises audio/visual content. Additionally, or alternatively, the one or more methods may comprise: accessing, by the processor, the camera of the mobile device; and initiating, by the processor, a prompt to capture the image of the identifier, wherein, optionally, the identifier is coupled to the object. In some such implementations, wherein the identifier comprises a marker coupled to the object.

In some of the foregoing implementations, the one or more methods may comprise: receiving, at the processor, a second image from the camera; and detecting, by the processor based on the second image, the object or a marker coupled to the object. Additionally, or alternatively, the one or more methods may comprise: tracking, by the processor, at least a portion of the marker in the plurality of images; determining position information associated with the marker in one or more images of the plurality of images; and displaying the 3D augmented reality content within the camera video stream based on the position information. In some such implementations, the one or more methods may also comprise: receiving, by the processor, placement data associated with the 3D augmented reality content; and determining, by the processor based on the position information and the placement data indicates, a position of the video content in relation to the 3D augmented reality content and/or one or more presentation characteristics of the video content.

In some of the foregoing implementations, the one or more methods may comprise: receiving text data, image data, or both at the mobile device from the server based on the identifier; displaying the text data, the image data, or both in the camera video content; and optionally, arranging the text data, the image data, or both based on the 3D augmented reality content. Additionally, or alternatively, the one or more methods may comprise sending, from the mobile device, a notification associated with a completion of the 3D augmented reality content, the video content, or both. In some such implementations, the one or more methods may also comprise: initiating a prompt to send a message based on a completion of the 3D augmented reality content, the video content, or both; receiving an input to send the message; and sending the message to the server, a device associated with a sender of the object, or both.

In some of the foregoing implementations, the one or more methods comprise: establishing communication with a server; and initiating, via the server, an order for delivery of an item to a recipient. In some such implementations, initiating the order comprises: generating order request information; and communicating the order information to a server. For example, generating the order request information may comprise: selecting the item; and selecting an option to deliver a multimedia message to the recipient. In such implementations, selecting the option to deliver the multimedia message may include: selecting order 3D augmented reality content; providing order video content; providing a text content; and/or providing an image. Additionally, or alternatively, the one or more methods may comprise: receiving confirmation of delivery of the item to the recipient; and/or receiving a notification that the multimedia message has been viewed.

In another aspect of the present disclosure, one or more devices include: a processor; and a memory storing one or more instructions that, when executed by the processor, cause the processor to: receive a plurality of images from a camera, at least one image of the plurality of images

5

including an object; display a camera video stream based on the plurality of images; display three dimensional (3D) augmented reality content in the camera video stream; and display video content based on the 3D augmented reality content, the video content associated with the object. In some such implementations, the one or more devices may further include: a display coupled to the processor; and/or the camera coupled to the processor. Additionally, the one or more instructions may be included in an application that is stored at the memory, and/or the memory may further be configured to store the 3D augmented reality content, the video content, or a combination thereof.

In some of the foregoing implementations, the one or more instruction, when executed by the processor, may further cause the processor to initiate storage at the memory of multimedia content presented via the display, the multimedia content associated with the camera video stream, the 3D augmented reality content, the video content, or a combination thereof. Additionally, or alternatively, in some of the foregoing implementations, the one or more devices may include: a network interface coupled to the processor, where the network interface comprises: a transmitter coupled to the processor, the transmitter configured to transmit one or more wireless signals; and/or a receiver coupled to the processor, the receiver configured to receive one or more wireless signals.

Some implementations of the present computer-readable storage mediums (e.g., computer-readable storage devices) store instructions that, when executed by a processor, cause the one or more processors to perform operations comprising: receiving, at a processor of a mobile device, a plurality of images from a camera, at least one image of the plurality of images including an object; displaying a camera video stream based on the plurality of images; displaying three dimensional (3D) augmented reality content in the camera video stream; and displaying video content based on the 3D augmented reality content, the video content associated with the object.

The foregoing has outlined rather broadly the features and technical advantages of the present disclosure in order that the detailed description that follows may be better understood. Additional features and advantages will be described hereinafter which form the subject of the claims. It should be appreciated by those skilled in the art that the conception and specific examples disclosed may be readily utilized as a basis for modifying or designing other structures for carrying out the same purposes described herein. It should also be realized by those skilled in the art that such equivalent constructions do not depart from the spirit and scope of the disclosure as set forth in the appended claims. The aspects which are characterized herein, both as to its organization and method of operation, together with further objects and advantages will be better understood from the following description when considered in connection with the accompanying figures. It is to be expressly understood, however, that each of the figures is provided for the purpose of illustration and description only and is not intended as a definition of the limits of the present disclosure.

BRIEF DESCRIPTION OF THE FIGURES

For a more complete understanding of the present example inventions, reference is now made to the following descriptions taken in conjunction with the accompanying figures, in which:

FIG. 1 illustrates an example of a system for providing multimedia content associated with delivery of a package;

6

FIG. 2 illustrates an example of an order form associated with providing multimedia content associated with delivery of a package;

FIG. 3 illustrates an example of a data structure associated with providing multimedia content associated with delivery of a package;

FIG. 4 illustrates an example of a package and a card associated with providing multimedia content;

FIG. 5 illustrates an example of displayed frames of multimedia content associated with delivery of a package;

FIG. 6 illustrates another example of displayed frames of multimedia content associated with delivery of a package;

FIG. 7 illustrates an example of a frame of multimedia content associated with delivery of a package;

FIG. 8 illustrates another example of a frame of multimedia content associated with delivery of a package;

FIGS. 9A, 9B, and 9C illustrate examples of frames of multimedia content associated with delivery of a package;

FIG. 10 illustrates another example of displayed frames of multimedia content associated with delivery of a package;

FIG. 11 illustrates an example of content from a mobile device displayed at an electronic device;

FIG. 12 illustrates a flow diagram of an example of a method of operating an electronic device;

FIG. 13 illustrates a flow diagram of an example of a method of operating a server; and

FIG. 14 illustrates a flow diagram of an example of a method of operating a mobile device.

DETAILED DESCRIPTION OF THE INVENTION

Particular implementations of the present disclosure are described below with reference to the drawings. In the description, common features are designated by common reference numbers throughout the drawings. As used herein, various terminology is for the purpose of describing particular implementations only and is not intended to be limiting of implementations. For example, the singular forms “a,” “an,” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise. It may be further understood that the terms “comprises” and “comprising” may be used interchangeably with “includes” or “including.” Additionally, it will be understood that the term “wherein” may be used interchangeably with “where.”

As used herein, an ordinal term (e.g., “first,” “second,” “third,” etc.) used to modify an element, such as a structure, a component, an operation, etc., does not by itself indicate any priority or order of the element with respect to another element, but rather merely distinguishes the element from another element having a same name (but for use of the ordinal term). The term “coupled” is defined as connected, although not necessarily directly, and not necessarily mechanically; two items that are “coupled” may be unitary with each other. The phrase “and/or” means and or. To illustrate, A, B, and/or C includes: A alone, B alone, C alone, a combination of A and B, a combination of A and C, a combination of B and C, or a combination of A, B, and C. In other words, “and/or” operates as an inclusive or.

Further, a device or system that is configured in a certain way is configured in at least that way, but it can also be configured in other ways than those specifically described. The feature or features of one embodiment may be applied to other embodiments, even though not described or illustrated, unless expressly prohibited by this disclosure or the nature of a described implementation.

Referring to FIG. 1, an example of a system 100 for delivering multimedia content associated with delivery of a package is shown. System 100 includes an electronic device 110, a server 130, a mobile device 150, and a distribution entity 180, each of which may be coupled via a network 190. Network 190 may include a wireless network, a wired network, or a combination thereof. For example, network 190 may include one or more of a local area network (LAN), metropolitan area network (MAN), wide area network (WAN), wireless LAN (WLAN), the Internet, intranet, extranet, cable transmission system, cellular communication network, and/or the like.

Electronic device 110 may include a network interface 112, one or more processors 114, a memory 116, and a camera 120. Network interface 112 may be configured to be communicatively coupled to one or more external devices, such as server 130 and/or mobile device 150, via one or more networks (e.g., 190). For example, network interface 112 may include a transmitter, a receiver, or a combination thereof (e.g., a transceiver). Memory 116 may store instructions 118, that when executed by the one or more processors 114, cause the processor(s) 114 to perform operations as described further here. For example, the one or more processors 114 may perform operations as described with reference to FIG. 12. In some implementations, memory 116 may store an application (e.g., a software program) associated with ordering and/or delivery of an item. Camera 120 may include an image capture device configured to generate image data, such as image data and/or video data. In some implementations, electronic device 110 may include one or more input/output (I/O) devices. The one or more I/O devices may include a mouse, a keyboard, a display device, the camera 120, other I/O devices, or a combination thereof.

Electronic device 110 may include or correspond to a communications device, a mobile phone, a cellular phone, a satellite phone, a computer, a tablet, a portable computer, a display device, a media player, or a desktop computer. Additionally, or alternatively, the electronic device 110 may include a set top box, an entertainment unit, a navigation device, a personal digital assistant (PDA), a monitor, a computer monitor, a television, a tuner, a radio, a satellite radio, a music player, a digital music player, a portable music player, a video player, a digital video player, a digital video disc (DVD) player, a portable digital video player, a satellite, a vehicle, any other device that includes a processor or that stores or retrieves data or computer instructions, or a combination thereof.

Server 130 may include a network interface 132, one or more processors 134, and a memory 136. Network interface 132 may be configured to be communicatively coupled to one or more external devices, such as electronic device 110, mobile device 150, and/or a device of distribution entity 180, via one or more networks (e.g., 190). For example, network interface 132 may include a transmitter, a receiver, or a combination thereof (e.g., a transceiver). Memory 136 may store instructions 138, preview content 139, order data 140. Instructions 138 may be configured to, when executed by the one or more processors 134, cause the processor(s) 134 to perform operations as described further here. For example, the one or more processors 134 may perform operations as described with reference to FIG. 13. In some implementations, memory 136 may store an application (e.g., a software program) associated with ordering an item for delivery. Preview content 139 may include pre-determined content for generating a preview of multimedia content (e.g., multimedia message preview 194). To illustrate, preview content may include pre-determined video

content of a representative package, and augmented reality content and/or video content 193 may be combined with preview content 139 to generate multimedia message preview 194. In some implementations, server 130 may provide multimedia message preview 194 to electronic device 110.

The order data 140 may include a data structure, such as a table, that includes order information (e.g., 192) for one or more orders. For example, each order may be arranged in the order data 140 as an entry 142. To illustrate, entry 142 may include at least a portion of order information 192. An illustrative example of order data 140 (e.g., entry 142) is described further herein with reference to FIG. 3. Additionally, or alternatively, memory 136 may be configured to additional data, such as content associated with a multimedia message as described further herein. For example, such content may include video content 193, AR content, text data, image data, or a combination thereof.

In some implementations, server 130 may comprise a general purpose processor-based system (e.g., PC and/or server system having a processor, memory, suitable I/O functionality, and OS) operating under control of an instruction set to interface with electronic device 110, mobile device 150, and/or distribution entity 180. In some implementations, server 130 may include one or more input/output (I/O) devices. The one or more I/O devices may include a mouse, a keyboard, a display device, the camera 120, other I/O devices, or a combination thereof.

Mobile device 150 may include a network interface 152, one or more processors 154, a memory 156, a camera 168, and a display 172. Network interface 152 may be configured to be communicatively coupled to one or more external devices, such as electronic device 110 and/or server 130, via one or more networks (e.g., 190). For example, network interface 152 may include a transmitter, a receiver, or a combination thereof (e.g., a transceiver). Memory 136 may store instructions 158 and application 160. Instructions 158 may be configured to, when executed by the one or more processors 154, cause the processor(s) 154 to perform operations as described further here. For example, the one or more processors 154 may perform operations as described with reference to FIG. 14.

Application 160 (e.g., a software program) may be associated with ordering and/or delivering an item. In some implementations, application 160 corresponds to an AR viewer and includes one or more sets of rules to perform operations as described herein for presenting multimedia content that includes AR content 162 included in a camera video stream (associated with images 170) and in which video content 193 is dynamically presented based on a position of camera 168 and further based on the AR content within the camera video stream. For example, the one or more sets of rules may direct the recipient to position a camera with respect to package 186 and to establish a coordinate system. Application 160 may include augmented reality (AR) content 162, placement data 163, or both. The placement data 163 may be used for presenting/positioning video content 193 within AR content 162. Additionally, placement data 163 may be used to modify characteristics, such as size and/or scale, of the video content 193. Camera 168 may include an image capture device configured to generate an image 170 (e.g., image data). For example, image 170 may include image data and/or video data. In some implementations, electronic device 110 may include one or more input/output (I/O) devices. The one or more I/O devices may include a mouse, a keyboard, a display device, the camera 120, other I/O devices, or a combination thereof.

Distribution entity **180** is configured to provide a system by which orders may be fulfilled and delivered. In some implementations, distribution entity **180** may include or correspond to a provider, an acquirer of goods and/or services, a distributor, and/or a shipper. For example, distribution entity **180** may be configured to package one or more items to be delivered to a recipient, and to initiate and/or deliver the package. In a particular implementation, server **130** corresponds to a provider (e.g., seller) of one or more items and distribution entity **180** corresponds to a shipping entity that includes an inventory of the one or more items and shipping media (e.g., boxes, envelopes, etc.). In such implementations, distribution entity **180** may deliver a package including one or more items or may operate with a third party for delivery of the package. Although described as being separate from server **130**, in other implementations, distribution entity may include server **130**.

Distribution entity **180** may include an electronic terminal **182**. Electronic terminal may comprise a general purpose processor-based system (e.g., PC and/or server system having a processor, memory, suitable I/O functionality, and OS) operating under control of an instruction set to interface with electronic device **110**, server **130**, and/or mobile device **150**. Electronic terminal **182** may include or correspond to a communications device, a mobile phone, a cellular phone, a satellite phone, a computer, a tablet, a portable computer, a display device, a media player, or a desktop computer. Additionally, or alternatively, the electronic terminal **182** may include a set top box, an entertainment unit, a navigation device, a personal digital assistant (PDA), a monitor, a computer monitor, a television, a tuner, a radio, a satellite radio, a music player, a digital music player, a portable music player, a video player, a digital video player, a digital video disc (DVD) player, a portable digital video player, a satellite, a vehicle, any other device that includes

During operation of system **100**, electronic device **110** may communicate with server **130** to initiate an order for delivery of an item. For example, electronic device **110** may access an order form as described with reference to FIG. 2. In such implementations, electronic device **110** may be associated with or correspond to a sender and/or requestor. In some implementations, the order form may be accessible via a web page or an application (e.g., **160**), such as an application stored at memory **116**. The application (e.g., a software component) may be associated with a provider, distributor, or shipper of the item. Additionally, or alternatively, the application may be associated with a third party that provides a platform or interface for the provider, distributor, or shipper. As an illustrative, non-limiting example, the application may be associated with a business that delivers items, such as flowers, food (e.g., cookies, fruit, etc.), or clothing. In some implementations, the application may include a social media/social networking feature, such that the sender/requester can communicate with the recipient via the application.

Electronic device **110** may generate order information **192** to initiate the order. For example, electronic device **110** may generate order information **192** to populate the order form. Order information **192** may include an indication of the item to be delivered, sender data (e.g., name, address, phone number, email address, payment information, etc.), recipient information (e.g., name, address, phone number, email address, etc.), a message, or a combination thereof.

Additionally, or alternatively, order information **192** may include or indicate that a multimedia message is to be made available to a recipient of the order. The multimedia message

may be associated with multimedia content that includes AR content and/or video content included in a camera video stream. In such implementations, order information **192** may include video content **193**. As used herein, video content **193** includes video data (e.g., a plurality of image), or video data and audio data. In some implementations, the sender/requestor may generate video content **193** via electronic device **110** (e.g., **120**) as part of filling out the order form. For example, the order form may be configured to prompt the sender/requestor to generate or provide the video content **193**. Although described as having the video content generated and/or provided with the order information **192** from the electronic device **110**, in other implementations, video content **193** may be generated and/or provided by server **130**, distribution entity (e.g., electronic terminal **182**), or another device or entity. To illustrate, when server **130** and/or distribution entity **180** correspond to a provider, the provider may include the video content **193** into the order information **192** to be used in a multimedia message. For example, if the sender/request does not request a multimedia message (that includes a personalized message for the recipient) with the order, the provider, distributor, and/or shipper may provide the video content **193**. Additionally, or alternatively, order information **192** may include a time value, such as a date, a time, a duration, etc., that corresponds to or defines a time period during which the multimedia content is available. To illustrate, the time period may start or be based on an order time when the order is submitted or a delivery time corresponding to delivery of a package (e.g., **186**) to a recipient, as illustrative, non-limiting examples. In other implementations, the multimedia content may be available for a predetermined time period (e.g., a pre-set time period).

Server **130** may receive the order information **192** and may generate entry **142** that corresponds to the order information **192**. In some implementations, the entry **142** may include an order number and/or identifier (e.g., **187**) that is configured to be used as an index to identify entry **142** within the order data **140**. Server **130** may also be configured to identify and store video content **193**. For example, video content **193** may be stored at memory **136** and included in entry **142**, at memory **136** at a location pointed to by entry **142**, or at a location remote from server **130** and identified by (e.g., pointed to) entry **142**. Although the order data **140** is described as being stored at server **130**, in other implementations, order data **140** may be stored at a remote location from server **130**, such as at a remote database, at distribution entity **180** (e.g., electronic terminal **182**), or at another location.

After receiving order information **192**, server **130** may send (e.g., via a push or a pull operation) an order request **195** to distribution entity **180** (e.g., electronic terminal **182**). The order request **195** may include at least a portion of the order information **192** and/or at least a portion of entry **142**. The distribution entity **180** may process the order request **195** to create a package **186** that includes one or more items. Package **186** may include the item or a shipping media, such as a box, a bag, crate, etc. In some implementations, package **186** may include or correspond to a package identifier (e.g., a package reference) that indicates characteristics of the package, such as dimensions, volume, weight restriction, etc. In such implementations, distribution entity **180** may communicate the package identifier and/or one or more characteristics of package **186** to server **130** and server **130** may optionally include such information in entry **142**.

The package **186** may include or be coupled to identifier **187**, a representation of identifier **187**, and/or a marker **188**.

11

To illustrate, identifier **187** may be represented as a bar code, a QC code, alphanumeric text, or a combination thereof, as illustrative, non-limiting examples. In some implementations, the identifier **187** may include or be the same as the marker **188**. In other implementations, the marker **188** may include an image, a logo, one or more points or features, etc. The identifier **187** and/or the marker **188** may be printed on the package **186** and/or item, printed on a card or sticker that is coupled to the package and/or item, as illustrative, non-limiting examples. In other implementations, the identifier **187** may include a digital or graphical representation that is communicated to a recipient or to a device (e.g., mobile device **150**) associated with the recipient.

Distribution entity **180** may initiate physical delivery of package **186** to recipient. For example, the recipient may receive a delivery including package **186** as described with reference to FIG. 4. Based on delivery of package **186** to recipient, distribution entity **180** (e.g., electronic terminal **182**) may send a delivery confirmation **196** to server **130**, electronic device **110**, and/or another device, such as another device associated with the sender. In some implementations, server **130** may receive delivery confirmation **196** and sent a confirmation message (based on delivery confirmation **196**) to a device (e.g., **110**) associated with sender.

The recipient may be associated with (e.g., be a user of) mobile device **150**. Based on receiving package **186**, recipient may operate mobile device **150** to access application **160**. In some implementations, application **160** includes an AR viewer. If mobile device **150** does not include application **160**, mobile device **150** may download application **160**, such as from server **130**. Processor **154** may execute one or more instructions of application **160** to perform operations described herein. To illustrate, processor **154** may access camera **168** and provide one or more images captured by camera **168** via display **172**. For example, the one or more images (e.g., **170**), such as a live video stream, may be provided to the display **172** and may be presented in real-time or near real-time. The displayed images presented in real-time or near real-time may be referred to as a camera video stream.

Processor **154** (e.g., application **160**) may provide a prompt to capture an image of identifier **187** and/or marker **188** and/or to enter or select an input that corresponds to identifier **187**. Processor **154** (e.g., application **160**) may detect identifier **187** and determine identifier data **197** based on the detected identifier **187**. For example, identifier data **197** may include a portion of image data. As another example, such as when identifier **187** includes a barcode, application may process barcode to determine a data value (e.g., **198**). Mobile device **150** may communicate identifier data **197** to server **130**. Responsive to receiving identifier data **197** (e.g., identifier **187**), server **130** may access entry **142** to identify video content **193** to be provided to mobile device **150** and may communicate the video content to mobile device **150**. In some implementations, server **130** may also communicate other information and/or data to mobile device **150** based on the received identifier data **197**. For example, server **130** may communicate text data, image data, AR content (or an identifier thereof) to mobile device **150** for use in providing multimedia content.

After transmission of the identifier data **197**, processor **154** (e.g., application **160**) may generate a prompt via display **172** for recipient to position camera **168** so marker **188** (e.g., package **186**) is presented in display **172**. For example, processor **154** initiate a target within display as described with reference to FIG. 5. By providing the target (e.g., a template) for the marker **188**, a user is able to

12

position the mobile device **150** in an initial position, orientation, and distance with respect to the marker **188**. The initial positioning of the mobile device **150** with respect to marker **188** may be known by the mobile device **150**. For example, application **160** may include initial positioning data, such as dimension of marker **188**, a distance between marker **188** and mobile device **150**, an orientation and/or translation of marker **188** with reference to a coordinate system implementation responsive to marker detection, etc.

Processor **154** may detect marker **188** and, in response to detection of the marker **188**, may implement a coordinate system with respect to the marker and initiate presentation of multimedia content including the AR content **162** and video content **193** in at least a portion of the video content stream. For example, processor **154** may display AR content **162** and video content **193** within camera video stream. In some implementations, the video content **193** is displayed in relation to and/or on a portion of the AR content. Examples of multimedia content are described herein at least with reference to FIGS. 5-10.

In some implementations, mobile device **150** includes presentation data **164** associated with a location (e.g., 3D position information) of video content **193** within the 3D AR content **162**. For example, the presentation data **164** may indicate or define a perimeter or boundary associated with presentation of video content **193**. The presentation data **164** may have an initial value that be calibrated to the coordinate system established based on detection of the marker **188**. The presentation data **164** may be utilized to display video content **193** for a time period during presentation of the multimedia message. For example, presentation of the video content **193** may be synchronized with the AR content **162**.

After detection of the marker **188**, mobile device **150** may be configured to track one or more characteristics of the marker **188** to determine a change in position (e.g., distance, rotation, translation) of mobile device **150** with respect to changes in features of the marker **188** (e.g., changes in size, angle, horizontal and/or vertical position within the display). Mobile device **150** may modify/update placement data **163** based on the determined change in position of the marker **188**. In some implementations, mobile device **150** may also generate a set of predicted presentation data values and select one of the predicted set of values to be used for presentation of video content **193**. The selected value(s) may be determined based on one or more inputs, such as motion data from a sensor (e.g., an inertial sensor) of mobile device **150**.

In some implementations, processor **154** may access a second camera of mobile device **150** to record a reaction of the recipient during presentation of the multimedia message. In such implementations, processor **154** may display a camera video stream corresponding to the second camera as described with reference to FIG. 10.

Based on presentation of the multimedia content, mobile device **150** (e.g., processor **154**) may send notification **198** that indicates presentation of the multimedia content. For example, mobile device **150** may send notification **198** to server **130** in response to initiation of the multimedia content, during the multimedia content, or in response to an end of the multimedia content. Based on notification **198**, server **130** may notify the sender/requester (via electronic device **110**) that the multimedia content has been provided to recipient.

In some implementations, after presentation of the multimedia content, processor **154** may provide a prompt, via display, to send one or more recordings, such as a recording of the multimedia content presented via display **172**, send a

second recording (e.g., recipient's reaction) associated with a second camera, and/or to record and send a reply message to sender. For example, processor 154 may provide a prompt as described with reference to FIG. 10. In response to a request to send the one or more recordings, processor 154 may send mobile device content 199 to server 130. Server 130 may store the one or more recordings which may be accessible to electronic device 110 via an application stored at memory 116. Electronic device 110 may play the one or more recordings. An example of the one or more recordings played via electronic device 110 is described with reference to FIG. 11.

One advantage provided by the system 100 is 3 that multimedia content (e.g., AR content 162 and/or video content 193) that corresponds to an object, such as package 186, may be made accessible to and/or delivered to the recipient. Mobile device 150 associated with the recipient is configured to implement a set rules (e.g., 160), such as an AR viewer application, that provided one or more conditions for establishing a coordinate system with respect to the package 186 and/or for dynamically determining video content placement data (e.g., 193) based on the coordinate system. To illustrate, the video content data for display may be determined as a function of marker characteristics and a movement prediction algorithm. Based on the video content placement data (e.g., 163), the set of rules are further configured to determine and implement video content presentation characteristics (e.g., orientation, translation, size, scale, perspective, etc.) to dynamically adjust the video content 193 for presentation. Accordingly, the video content 193 may be efficiently presented with a live video stream (e.g., 170) such that the video content 193 interacts with the AR content 162 included in the live video stream. The displayed video content may further be presented based on movement and placement of at least a portion of the AR content 162 such that occlusion and collision algorithm further coordinate and/or synchronize movement of the mobile device 150 with presentation of the AR content 162 and the video content 193 within the live video stream (e.g., 170). Thus, the present disclosure advantageously provides multimedia content by establishing a coordinate system in a controlled manner such that the one or more rules may be efficiently applied to dynamically determine adjustments/updates to presentation data associated with the video content 193 and to select the placement data 163 based at least on features of marker 188 and/or movement or predicted movement of mobile device 150.

Referring to FIG. 2, an example of an order form 210 is shown. Order form 210 includes one or more categories 220, such categories 222-238, and one or more corresponding fields 240, such as fields 242-258. Fields 240 may be populated via user input and may be configured to receive text data, an indication of a file location, an input via a selectable option of the field, etc.

The one or more categories 220 may include a sender 222, an item(s) 224, a recipient 226, a contact 228, an address 230, AR content 232, video content 254, message 236, and an access code 238. Sender field 242 may be populated with a name, user name, account number, address, contact information, etc. associated with an individual or entity. For example, the individual or entity may be associated with populating and/or submitting order form 210. Item(s) field 244 may be populated with one or more items to be delivered to an recipient, such as a user of mobile device 150. As illustrative, non-limiting examples, the one or more items may include a consumable good (e.g., cookies, fruit, a sandwich, alcohol, etc.), clothing (e.g., shoes, a shirt, a hat,

etc.), a promotional item (e.g., a poster, a book, a pamphlet, etc.), and/or another item. Recipient field 246 may be populated with a name, user name, account number, etc., associated with an individual or entity to receive the one or more items identified in item(s) field 244. Contact field 248 may be populated with a phone number, email address, etc. associated with the recipient. Address field 250 may be populated with a physical address, location description, directions, passcode, etc. associated with delivering the one or more items to the recipient.

AR content field 252 may be populated to indicate AR content is to be provided in a multimedia message that is made available to and/or presented to at least the recipient. In some implementations, AR content field 252 may include one or more selectable options of AR content (e.g., 162). To illustrate, a first option may correspond to a first animated character, a second option may correspond to a second animated character, and a third option may correspond to a holiday theme, as illustrative, non-limiting examples. Video content field 254 may be populated to include or identify video content (e.g., 193) to be included in the multimedia message. To illustrate, video content field 254 may provide one or more options for the sender to record or attach video content (e.g., a video message). Message field 256 may be populated with text data, an image, or a combination thereof. Access code field 258 may be populated with security data, such as a passcode (e.g., password), security phase and/or security answer, etc. The access code field 258 may be populated with the security data to limit or restrict access to the multimedia content. To illustrate, the security data may be known by the recipient, or may be provided to the recipient, and may be required to be provided in order for the recipient to receive a portion or an entirety of the multimedia message, such as the video content (e.g., 193) and/or the message (associated with message field 256). For example, if the security data is not known by the recipient, the security data may be provided to the recipient, such as via text message, phone message, email, etc. In some implementations, the security data may be provided to the recipient based on delivery of the one or more items (e.g., package 186). Referring to FIG. 1, server 130 may be configured to communicate security data to mobile device 150 in response to receiving delivery confirmation 196. Additionally, or alternatively, access code field 258 may provide options to limit or restrict the number of times the multimedia message can be viewed, whether the multimedia message is recordable, how long the multimedia message is available/accessible, etc.

Although order form 210 has been described as including particular fields (e.g., 242-258), such fields and descriptions are for illustration purposes and are not intended to be limiting. For example, order form 210 may include more fields or fewer fields than described. To illustrate, in some implementations, order form 210 further includes a delivery time field associated with a requested time of delivery (e.g., date, time, etc.) of the one or more items to the recipient. Additionally, or alternatively, one or more of fields 242-258 may include multiple subfields.

Thus, FIG. 2 illustrates an example of an order form 210 to enable a sender to initiate a multimedia message to be made available to a receiver of one or more items (e.g., package 186). For example, order form 210 is configured to enable a sender (e.g., a requester) to provide video content (e.g., 193) to be incorporated into the multimedia message and displayed in relation to and/or with AR content. Additionally, order form 210 beneficially enables a security

15

feature to be provided with the multimedia message to restrict or limit access to and/or dissemination of the multimedia message.

Referring to FIG. 3, an example of order data 140 is shown. Order data 140 may be generated by, stored at, and/or maintained by one or more servers, such as server 130. Order data 140 includes one or more entries, such as entry 142. Entry 142 includes one or more fields. The one or more fields may include an order number 310, an item(s) ID 312, sender information 314, recipient information 316, an AR content ID 318, a video content ID 320, a message ID 322, and an identifier field 324 (corresponding to identifier 187). Item(s) ID 312 may include or correspond to the one or more items identified and/or described with reference to item(s) field 244. Sender information 314 may include or correspond to information included in sender field 242. Recipient information 316 may include or correspond to information included in recipient field 246, contact field 248, and/or address field 250.

AR content ID 318 may include AR content (e.g., 162), an AR content identifier (of a plurality of AR content identifiers) and/or an indication of a storage location of AR content. For example, a first AR content identifier may correspond to a first animated character, a second AR content option may correspond to a second animated character, a third AR content identifier may correspond to a birthday theme, and a fourth AR content identifier may correspond to a get well theme, as illustrative, non-limiting examples. Video content ID 320 may include video data (e.g., video content 193) or an indication of a storage location of the video data. For example, the video data may include or correspond to data included in video content field 254. Message ID 322 may include message data or an indication of a storage location of the message data. For example, the message data may include or correspond to data included in message field 256.

Although entry 142 is described as including each of the fields 310-324, in other implementations, entry 142 may include fewer fields or more fields. To illustrate, in a particular implementation, entry 142 may not include AR content ID 318 and/or may include an access code field associated with access code field 258. Additionally, or alternatively, one or more of fields 310-324 may include multiple subfields.

Thus, FIG. 3 illustrates an example of order data 140 that is associated with delivery of a package (e.g., 186) and a corresponding multimedia message. For example, order data 140 may enable a server to provide order request 195 to distribution entity 180 and to provide AR content 162 and/or video content 193 to mobile device 150. Additionally, in some implementations, order data 140 (e.g., entry 142) enables server 130 to provide information, such as delivery confirmation 196 and/or mobile device content 199 to electronic device 110 associated with the sender.

Referring to FIG. 4, an example of a delivery 400 is shown. Delivery 400 includes package 186 and, optionally, a card 410 (e.g., an insert). Package 186, card 410, or both may include identifier 187, such as a barcode, a QR code, text, or a combination thereof, as illustrative, non-limiting examples. As shown, card 410 includes a text portion 412. Text portion 412 may include instructions directing the recipient of package 186 on how to receive (e.g., access) the multimedia content. For example, text portion 412 may direct the recipient to download and/or access application 160. Using application 160, recipient may scan (using camera 168) identifier 187. Additionally, or alternatively, text portion 412 may provide instructions for the recipient to access preview content (e.g., multimedia message preview

16

194) via server 130. For example, in situations where the recipient does not have access to a mobile device and/or does not have the ability to access application 160 or a camera (e.g., 168), the text portion 412 may provide instructions for the recipient to access, such as via a website, multimedia message preview 194. Thus, FIG. 4 provides an illustrative example of delivery 400 that includes marker 188 and/or identifier 187 to a recipient to enable presentation of multimedia content as described herein.

Referring to FIGS. 5-10, examples of displayed frames of multimedia content associated with delivery of a package (e.g., 168) are shown. For example, one or more of the frames may include or correspond to at least a portion of a camera video stream (e.g., 170) into which AR content (e.g., 162) and video content (e.g., 193) is added. To illustrate, the camera video stream may include or correspond to one or more images 170, and the one or more frames may be displayed via a display, such as display 172, of a device. The device may include electronic device 110 or mobile device 150, as illustrative, non-limiting examples. To illustrate, one or more frames of FIGS. 5-10 may be generated by an application, such as application 160.

As described with reference to FIGS. 5-10, an application (e.g., 160) may be configured to access and/or operate one or more cameras, process one or more images, and/or perform one or more image processing operations, such as object detection, object recognition, object tracking (using a marker or marker-less), or a combination thereof, as illustrative, non-limiting examples. Additionally, as described herein, the camera video stream may be presented in real-time or near real-time such that a user viewing display 172 does not perceive a noticeable delay between a change in position and/or orientation of a camera and presentation of the camera video stream (produced based on a field of view of the camera). In some implementations, a delay in presentation of the camera video stream may be noticeable and may still be considered near real-time. To illustrate, such delays may be based on a processing capability and/or image rendering capability of a device (e.g., 110, 150) that includes the camera. It is noted that one or more frames of and/or one or more operations described with reference to one of the methods of FIGS. 5-10 may be combined with one or more frames of and/or one or more operations of another of FIGS. 5-10. For example, one or more frames of FIG. 4 may be combined with one or more frames of FIG. 6. As another example, one or more frames of FIGS. 5-6 may be combined with the frame of FIG. 8. As another example, one or more frames of FIGS. 9A-9C may be combined with the frame of FIG. 7. As another example, one or more frames of FIG. 5-6 or 9A-9C may be combined with one or more frames of FIG. 10.

Referring to FIG. 5, an example of a series of frames 500 presented via display 172 is shown. A first frame 510 of the series 500 displays a target 512. In some implementations, target 512 may be presented based on accessing application 160, detecting identifier 187, communicating identifier data 197 to server 130, receiving video content 193, or a combination thereof. Target 512 may be configured to aid a user in aligning a marker (e.g., 188) within a field of view of a camera. In some implementations, target 512 may include a bracket, line, and/or border to frame (e.g., outline) the marker, a transparent representation of the marker, or a combination thereof, as illustrative, non-limiting examples.

A second frame 520 of series 500 includes target 512 positioned over marker 188 of package 186. For example, package 186 may be included in a camera video stream (e.g., 170) presented via display 172. Application 160 may per-

17

form objection recognition/detection on second frame 520 to identify marker 188. Based on detecting marker 188, the application may determine a position of marker 188, establish a coordinate system based on marker 188, identify one or more edges of box (e.g., 186), perform object tracking on marker 188 and/or package 186, or a combination thereof. Additionally, or alternatively, in response to detection of marker 188, application 160 may remove target 512 from display 172 and/or may initiate presentation of the multimedia message including AR content 162 and video content 193.

A third frame 530 of series 500 includes AR content 162, such as a 3D animated character, within third frame 530. The character is displayed at a first position within the camera video stream (e.g., 170) that includes package 186. To illustrate, between second frame 520 and third frame 530, the animated character may move to the first position on package 186. As illustrative, non-limiting examples, the animated character may have appeared out of thin air, dropped down onto package 186, parachuted onto package 186, or climbed onto package 186. A fourth frame 540 of series 500 shows the character (e.g., 162) at a second position within the camera video stream. For example, between third frame 530 and fourth frame 540, the character may have walked from the first position towards the second position and tripped over marker 188. In other implementations, the character may tripped over another object included in the camera video stream, such as a ribbon (not shown) that is coupled to or incorporated into package 186.

A fifth frame 550 of series 500 includes the animated character at a third position within the camera video stream and additional AR content 162, such as a monitor (e.g., a television), at a fourth position within the camera video stream. In fifth frame 550, animated character includes a remote control in one hand. To illustrate, between fourth frame 540 and fifth frame 550, the animated character may have produced the remote control and operated the remote control to cause the monitor to be included (e.g., drop down onto or raise up from package 186) in the camera video stream. The monitor may have a screen 552 that is associated with or corresponds to video content 193 to be displayed. In some implementations, a boundary/perimeter of screen 552 may include or correspond to the placement data 163.

A sixth frame 560 of series 500 includes the AR content 162 (e.g., animated character and monitor) included within the camera video stream. Sixth frame 560 also includes video content 193 within camera video stream and positioned based on AR content 162. For example, video content 193 is positioned within the monitor such that video content 193 is presented via screen 552 of the monitor. To further illustrate, between fifth frame 550 and sixth frame 560, the animated character may have operated the remote control to cause video content 193 to be presented via screen 552 of the monitor.

Thus, FIG. 5 illustrates aspects of initiation and presentation of the multimedia message via display 172. The multimedia message may present the AR content 162 in the camera video stream. Additionally, the multimedia message may present the video content 193 in relation to the AR content.

Referring to FIG. 6, an example of a series of frames 600 presented via display 172 is shown. A first frame 610 of the series 600 is associated with a camera video stream (e.g., 170) and includes card 410 having identifier 187. Based on first frame 610, application 160 may detect identifier 187 and send identifier data 197 to server 130. In other implementations, identifier 187 may be coupled to package 186

18

and first frame 610 may include identifier 187 coupled to package 186. Responsive to sending identifier data 197 to server 130, mobile device 150 may receive AR content 162, video content 193, and/or other content (e.g., text data and/or image data) from server 130.

A second frame 620 of the series 600 includes package 186 including marker 188. Prior to second frame 620, application 160 may have detected and identified marker 188. For example, first frame 610 and second frame 620 of series 600 of FIG. 5 may have occurred between first frame 610 and second frame 610 of series 600.

A third frame 630 of series 600 includes AR content 162, such as a ladder, within third frame 630. To illustrate, between second frame 620 and third frame 630, the ladder may have propped against a side of package 186. A fourth frame 640 of series 600 shows AR content 162 including the ladder and the animated character. To illustrate, between third frame 630 and fourth frame 640, the animated character may have climbed up a portion of the ladder towards a top surface of package 186. A fifth frame 650 of series 600 includes the animated character at a first position on the top surface of package 186. To illustrate, between fourth frame 640 and fifth frame 650, the animated character may have climb off of the ladder onto the top surface of package 186 and moved to the first position. A sixth frame 660 of series 600 includes the AR content 162, such as the ladder, the animated character, and the monitor. Sixth frame 660 also includes video content 193 positioned based on AR content 162. For example, video content 193 is positioned within the monitor such that video content 193 is presented via a screen of the monitor. To further illustrate, between fifth frame 650 and sixth frame 660, the monitor may have been included in the camera video stream and animated character may have moved to a second position as shown in sixth frame 660.

Thus, FIG. 6 illustrates aspects of initiation and presentation of the multimedia message via display 172. For example, FIG. 6 illustrates detection of identifier 187 and presentation of AR content 162 in the camera video stream. Additionally, FIG. 6 illustrates presentation of the video content 193 based on (e.g., within) the AR content 162.

Referring to FIG. 7, an example of a frame 700 included in a series of frames (associated with a multimedia message) presented via display 172 is shown. As shown, frame 700 includes package 186 AR content 162, such as an animated character and a monitor (e.g., a television). Video content 193 is positioned within the monitor such that video content 193 is presented via a screen of the monitor. The AR content 162 also includes a sign 702 (e.g., a card). Sign 702 includes one or more portions, such as a first portion 710 including text content and a second portion 712 including an image, such as a logo, picture, graphic, etc. The content included in first portion 710, second portion 712, or both, may include or correspond to message field 256 and or message ID 322. Sign 702 may be included in the camera video content prior to, during (e.g., a portion or an entirety), and/or after presentation of video content 193. Thus, FIG. 6 illustrates aspects of presentation of the multimedia message via display 172.

Referring to FIG. 8, an example of a frame 800 included in a series of frames (associated with a multimedia message) presented via display 172 is shown. As shown, frame 800 includes package 186 and AR content 162, such as an animated character and a sign 802 (e.g., a card). Sign 802 includes one or more portions, such as a first portion 810, a second portion 812, and a third portion 814. First portion 810 includes text content, second portion 812 includes an image, such as a logo, picture, graphic, etc., and third portion

19

814 includes video content **193**. The content included in first portion **810**, second portion **812**, or both, may include or correspond to message field **256** and or message ID **322**. Thus, FIG. 7 illustrates aspects of presentation of the multimedia message via display **172**.

Referring to FIGS. 9A-9C, examples of AR content **162** in which video content **193** is presented are shown. To illustrate, each of the examples of FIGS. 9A-9C enable at least a portion video content **193** to be viewed over a range of camera positions and/or camera orientations. For example, each of FIGS. 9A-9C include a first frame associated with a first camera pose (e.g., a first position and a first orientation of camera **168** with respect to package **186** (e.g., marker) and a second frame associated with a second camera pose (e.g., a second position and a second orientation of camera **168** with respect to package **186** (e.g., marker **188**)). In some implementations, the first camera pose is associated with a front view of package **186** and the second camera pose is associated with a rear view of package **186**. In each of the first frame and the second frame, a portion and/or version of video content **193** is visible to a user such that movement/positioning of the camera by the user is not limited in order to view the video content **193** of the multimedia message.

Referring to FIG. 9A, an example of a series of frames **900** (associated with camera video stream **170**) presented via display **172** is shown. A first frame **910** of the series **900** includes a frame of camera video stream (e.g., **170**) captured by camera (e.g., **168**) at a first position and first orientation with respect to package **186** (e.g., marker **188**). For example, first frame **910** may correspond to a first camera pose associated with camera **168**. First frame **910** includes AR content **162**, such as the animated character, a projector, and a projection screen. As shown, a front view of video content **193** is presented on the projection screen that is flat. The video content may be positioned and/or sized in relation to the AR content **162** (e.g., the projection screen) based on the first camera pose, such as the first position and orientation of camera **168**.

A second frame **920** of the series **900** includes another frame of camera video stream captured by camera **168** at a second position and a second orientation with respect to package **186** (e.g., marker **188**). For example, second frame **920** may correspond to a second camera pose associated with camera **168**. Second frame **920** includes AR content **162**, such as the animated character, the projector, and the projection screen. As shown, video content **193** is presented on the projection screen. As compared to first frame **910**, video content **193** displayed in second frame **920** is a reverse image (e.g., a rear view) of video content **193** displayed in first frame **910**.

Referring to FIG. 9B, an example of a series of frames **900** (associated with camera video stream **170**) presented via display **172** is shown. A first frame **940** of the series **930** is associated with the first camera pose and a second frame **950** of the series **930** is associated with the second camera pose. Each of the first and second frames **940**, **950** includes AR content **162**, such as the animated character, the projector, and the projection screen. As shown, the projection screen has a curved surface. In other implementations, the projection screen may have different size, shape, and/or geometry. For example, the projection screen may be disc shaped (e.g., semi-spherical).

Referring to FIG. 9C, an example of a series of frames **960** (associated with camera video stream **170**) presented via display **172** is shown. A first frame **970** of the series **960** is associated with the first camera pose and a second frame **980**

20

of the series **960** is associated with the second camera pose. Each of the first and second frames **970**, **980** includes AR content **162**, such as the animated character and a three-dimensional (3D) structure of multiple screens. For example, as shown in first frame **970**, the multi-screen structure includes a front screen and a side screen. In some implementations, a top surface **972** of the multi-screen structure may include text content or an image (e.g., a logo). As shown in second frame **980**, the multi-screen structure includes the side screen and a rear screen. Each of the screens of the multi-screen structure may include video content **193**. To illustrate, video content **193** presented via each screen of the multi-screen structure may be synchronized in time.

Referring to FIG. 10, an example of a series of frames **1000** presented via display **172** is shown. A first frame **1010** of the series **1000** displays target **512** in a camera video stream corresponding to a first camera (e.g., **168**). Target **512** may be configured to enable a user to align a marker (e.g., **188**) within a field of view of the first camera. First frame **1010** also includes a user portion **1012** associated with a second camera video stream of a second camera. To illustrate, mobile device **150** may include multiple camera, such as a front facing camera (e.g., first camera) and a rear facing camera (e.g., second camera). As shown, user portion **1012** includes a target (e.g., dashed line).

A second frame **1020** of series **1000** includes target **512** positioned over marker **188** of package **186**. For example, package **186** may be included in a camera video stream (e.g., **170**) presented via display **172**. An application (e.g., **160**) may perform objection recognition/detection on second frame **520** to identify marker **188**. Based on detecting marker **188**, the application may determine a position of marker **188**, establish a coordinate system based on marker **188**, identify one or more edges of box (e.g., **186**), perform object tracking on marker **188** and/or package **186**, or a combination thereof. Additionally, as shown, a face of the user is included user portion **1012**. In some implementations, application **160** may detect that an object (e.g., a face) is present in second camera video stream. Based on identification of marker **188** and/or detection of both marker **188** and the object (e.g., a face), application **160** may initiate presentation of AR content (e.g., **162**) and/or video content (e.g., **193**) within first camera video stream (e.g., **170**). In some implementations, based on identification of marker **188** and/or detection of both marker **188** and the object (e.g., a face), application **160** may initiate a first recording corresponding to presentation of AR content (e.g., **162**) and/or video content (e.g., **193**) within first camera video stream (e.g., **170**). Additionally, or alternatively, based on identification of marker **188** and/or detection of both marker **188** and the object (e.g., a face), application **160** may initiate a second recording corresponding to second camera video stream.

A third frame **1030** of series **1000** includes AR content **162**, such as a 3D animated character at a first position, within third frame **1030**. To illustrate, between second frame **520** and third frame **530**, target **512** and the target of user portion **1012** have been removed, and the animated character may be presented on package **186**. As compared to second frame **1020**, user portion **1012** has a reduced size to make more of the first camera video stream (and AR content) visible via display **172**.

A fourth frame **1040** of series **1000** shows AR content **162** that includes animated character (at a second position) and a monitor (e.g., a television) within the first camera video stream. In fourth frame **1040**, animated character includes a

21

remote control in one hand and video content **193** is presented and positioned based on AR content **162**. For example, video content **193** is positioned within the monitor such that video content **193** is presented via a screen of the monitor.

A fifth frame **1050** of series **1000** shows the animated character at a third position. To illustrate, between fourth frame **1040** and fifth frame **1050**, the animated character moved from the second position (e.g., a lower left portion of display **172**) to the third position (e.g., a lower right portion of display **172**). Based on the movement of the animated character between fourth frame **1040** and fifth frame **1050**, application **160** may have adjusted a characteristic of user portion **1012**. For example, the characteristic of user portion **1012** may include a size, a shape, a position, a location, a transparency, another characteristic, or a combination thereof. As shown in fifth frame **1050**, user portion **1012** is positioned in the lower right of display **172** as compared to being displayed in the lower right of display **172** in fourth frame **1040**. In some implementations, application **160** may adjust the characteristic of user portion **1012** in response to a determination that at least a portion of or an entirety of the character is within a threshold distance of user portion **1012**.

A sixth frame **1060** of series **1000** includes the AR content **162** (e.g., animated character and a sign **1064**). Sixth frame **1060** may be presented after completion of the video content **193**. In some implementations, sixth frame **1060** may be presented after application **160** stopped storing the first recording and/or the second recording. The sign **1064** may include a portion **1066** that includes a message for the user. For example, the message may indicate an option for the user to provide a reply message to a sender of package **186**. To illustrate, the replay message may include the first recording, the second recording, a text message (e.g., a static message or a dynamic/scrolling message), a video message recorded by the user (e.g., a pre-recorded or existing video), or a video recorded after presentation of the multimedia content including the AR content **162** and the video content **193**, an audio clip, or a combination thereof. In a particular implementation, application **160** may control the second camera and display **172** to enable the user to record a reply video message for the sender.

Thus, FIG. **10** illustrates aspects of presentation of the multimedia message via display **172**. For example, as described with reference to FIG. **10**, first and/or second recordings may be generated in association presentation of the multimedia content. The first and/or second recordings may be available to the user (e.g., recipient) for replay or transmission/posting for another user (i.e., sender). In some implementations, an option to record an additional message and/or video content may be presented to the user (e.g., recipient).

Referring to FIG. **11**, an example of a series of frames **1100** presented via a display **1112** is shown. Display **1112** may include or correspond to a display of a device, such as electronic device **110** or mobile device **150**. The series of frames **1100** may include or correspond to playback of recorded content, such as content recorded at the same device or a different device. For example, the recorded content may include or correspond to mobile device content **199**.

A first frame **1110** of the series **1100** includes a first portion **1114** and a second portion **1116**. First portion **1114** may include or correspond to a first recording, such as a recording of multimedia content presented at mobile device **150**. Second portion **1116** may include or correspond to a

22

second recording, such as recording of a user of mobile device **150** during presentation of the multimedia content at mobile device **150**. For example, the second recording may include or correspond to content displayed via user portion **1012**. As shown, first frame **1110** shows first scenes of each of the first recording (presented in first portion) and second recording (presented in second portion). In some implementations, presentation of the first and second recordings via display **1112** may be time synchronized.

A second frame **1120** of series **1100** shows second scenes of each of the first recording (presented in first portion) and second recording (presented in second portion). For example, as shown, second frame **1120** shows the animated character (in first portion **1114**) after the animated character tripped, and shows a reaction of the user (in second portion **1116**) responsive to observing that the animated character tripping. A third frame **1130** of series **1100** shows third scenes of each of the first recording (presented in first portion) and second recording (presented in second portion). For example, as shown, third frame **1130** shows the animated character and the monitor including video content (in first portion **1114**), and shows the user (in second portion **1116**). A fourth frame **1140** of series **1100** shows fourth scenes of each of the first recording (presented in first portion) and second recording (presented in second portion). In some implementations, the fourth scenes may be associated with an end of the first and second recordings.

A fifth frame **1150** of series **1100** shows a recorded video message from the user (e.g., the receiver) to the sender. For example, the message may have been recorded after the user viewed the multimedia content. Although FIG. **11** has been described as presenting three different recordings, in other implementations, fewer than three or more than three recordings may be presented.

Thus, FIG. **11** illustrates describes playback of recorded content associated with the multimedia message. To illustrate, a first recording presented via first portion **1114** includes the multimedia message as presented to the recipient and second recording presented via second portion **1116** include the recipient's demeanor/reaction during presentation of the multimedia message. The third recording presented after the first and second recordings includes a message from the recipient to the sender.

Referring to FIG. **12**, a method **1200** of operating an electronic device is shown. For example, method **1200** may be performed by electronic device **110**, mobile device **150**, or electronic terminal **182**.

Method **1200** may include initiating, at the electronic device, an order request via a server, at **1502**. For example, the order request may include or correspond to order form **210**. The server may include or correspond to server **130**.

Method **1200** includes generating order information by the electronic device, at **1204**. For example, the order information may include or correspond to order information **192**, input(s) provided to one or more fields **242-258**, or a combination thereof. To illustrate, generating (e.g., **1204**) the order information may include selecting an item, at **1206**, providing sender information and recipient information, at **1208**, and requesting a multimedia message, at **1210**. Requesting (e.g., **1210**) the multimedia content may include selecting augmented reality content, at **1212**, providing video content, at **1214**, providing a text message, at **1216**, providing an image, at **1218**, or a combination thereof. For example, the augmented reality content and the video content may include or correspond to AR content **162** and video content **193**, respectively.

Method **1200** may include receiving, at the electronic device, a multimedia message preview from the server, at **1220**. The multimedia message preview may include or correspond to preview content **139**. Method **1200** includes submitting, by the electronic device, the order request to the server, at **1222**. The order request may include or correspond to order information **192** and/or order form **210**.

Method **1200** may include receiving, at the electronic device, a delivery confirmation, at **1224**. The delivery confirmation, such as delivery confirmation **196**, may correspond to delivery of a package that includes at least one item identified in the order request. For example, the package may include or correspond to package **186** delivered by distribution entity **180**.

Method **1200** may include receiving, at the electronic device, mobile device content associated with the multimedia message, at **1226**. For example, the mobile device content may include or correspond to mobile device content **199** and/or series of frames **1100**. Method **1200** may include presenting the mobile device content via a display device of the electronic device, at **1228**. Thus, method **1200** may enable operation of an electronic device (e.g., **110**, **150**) to order delivery of an item to a recipient and to be notified of delivery of multimedia content associated with the delivery.

Referring to FIG. **13**, a method **1300** of operating a server is shown. For example, method **1300** may be performed by server **130**. Method **1300** may include receiving, by the server from an electronic device, an order request for an item, at **1302**. For example, the order request may include or correspond to the order information **192** or order form **210**. The electronic device may include or correspond to electronic device **110**, mobile device **150**, or electronic terminal **182**. The order request may be associated with video content, such as video content **193**.

Method **1300** may include initiating storage of the video content by the server, at **1304**. To illustrate, the server may initiate storage of the video content at a memory, such as memory **136**, that is accessible to the server. In some implementations, the server may receive the video content from a device, such the electronic device that that initiated the order request. In other implementations, the server may receive the video content from a manufacturer, provider, supplier, and/or distributor of the item, a delivery service or shipper of a package that includes the item, or another device or entity.

Method **1300** may include generating an order entry by the server, at **1306**. For example, the order entry may include or correspond to entry **142**. Generating (e.g., **1306**) the order entry may include generating an order number, at **1308**, generating an identifier corresponding to the order number, at **1310**, or both. The order number may include or correspond to order number **310**. The identifier may include or correspond to identifier **187**, marker **188**, or a combination thereof.

Method **1300** may include providing, by the server, an order request to a distribution entity, at **1312**. For example, the order request may include or correspond to order request **195**, and the distribution entity may include or correspond to distribution entity **180**. Method **1300** may include receiving, by the server, confirmation of delivery of a package correspond to the order request, at **1314**. For example, the confirmation may include or correspond to delivery confirmation **196**. In some implementations, the server may receive the confirmation from distribution entity **180** and/or may send the confirmation to a device, such as a device that initiated the order request.

Method **1300** may include receiving, by the server, identifier data from a mobile device, at **1316**. For example, the identifier data may include or correspond to identifier data **197**, and the mobile device may include or correspond to mobile device **150**. The identifier data may include or correspond to identifier **187**. Method **1300** includes identifying, by the server, the order entry based on the identifier data, at **1318**. To illustrate, the server may identify and/or access entry **142** based on identifier data. Method **1300** further includes initiating, by the server, transmission of the video content to the mobile device, at **1320**.

Method **1300** may also include receiving, at the server from the mobile device, a notification of presentation of a multimedia message, at **1322**. For example, the notification may include or correspond to notification **198**. The multimedia message may be associated with the order request and may include the video content and augmented reality content, such as 3D augmented reality content. To illustrate, multimedia message may include or correspond to mobile device content **199**. In some implementations, the notification includes mobile device content **199**. In such implementations, the server may provide the notification and/or the mobile device content **199** to a device, such as a device that initiated the order request. Thus, method **1300** describes operation of server (e.g., **130**) to enable delivery of an ordered item to a recipient, delivery of multimedia content to the recipient, and notification of delivery of the multimedia content.

Referring to FIG. **14**, a method **1400** of operating a server is shown. For example, method **1400** may be performed by electronic device **110**, mobile device **150**, or electronic terminal **182**.

Method **1400** includes receiving, at a mobile device from a server, video content corresponding to an identifier, at **1402**. For example, the server may include or correspond to server **130**, and the video content may include the video content **193**. The identifier may be associated with a package. To illustrate, the identifier may include or correspond to identifier **187** associated with package **186**.

Method **1400** include receiving, at the mobile device, a plurality of images including at least a portion of the package, at **1404**. The plurality of images may correspond to a camera video stream. For example, the plurality of images may include or correspond to the one or more images **170**.

Method **1400** includes generating, at the mobile device, multimedia content associated with the package, **1406**. Generating (e.g., **1406**) may include displaying the camera video stream by the mobile device, at **1408**. Generating (e.g., **1406**) may also include displaying, by the mobile device, augmented reality content within at least a portion of the displayed camera video stream, at **1410**, and displaying, by the mobile device, the video content in relation to the augmented reality content, at **1412**. The augmented reality may include or correspond to AR content **162**.

In some implementations, the multimedia content associated with the package may be generated at a different device, such as at server **103**. In such implementations, the sever may transmit (e.g., stream) the multimedia content to the mobile device for presentation via a display.

Thus, method **1400** describes operation of a device (e.g., **110**, **150**) to enable delivery of a multimedia message that corresponds to delivery of a package (e.g., an item). The multimedia message may adventurously display AR content and video content in a live video stream generated by a camera of the device.

The operations described with reference to the methods of FIGS. **12-14** may be controlled by one or more processing

25

unit such as a central processing units (CPUs), controllers, field-programmable gate array (FPGA) devices, application-specific integrated circuits (ASICs), other hardware devices, firmware devices, or any combination thereof. It is noted that one or more operations described with reference to one of the methods of FIGS. 12-14 may be combined with one or more operations of another of FIGS. 12-14. For example, one or more operations of method 1200 may be combined with one or more operations of method 1300. As another example, one or more operations of method 1200 may be combined with one or more operations of method 1400.

Although one or more of the disclosed figures may illustrate systems, apparatuses, methods, or a combination thereof, according to the teachings of the disclosure, the disclosure is not limited to these illustrated systems, apparatuses, methods, or a combination thereof. One or more functions or components of any of the disclosed figures as illustrated or described herein may be combined with one or more other portions of another function or component of the disclosed figures. Accordingly, no single implementation described herein should be construed as limiting and implementations of the disclosure may be suitably combined without departing from the teachings of the disclosure.

Although the present disclosure and its advantages have been described in detail, it should be understood that various changes, substitutions and alterations can be made herein without departing from the spirit and scope of the disclosure as defined by the appended claims. Moreover, the scope of the present application is not intended to be limited to the particular embodiments of the process, machine, manufacture, and composition of matter, means, methods and steps described in the specification. As one of ordinary skill in the art will readily appreciate from the disclosure, processes, machines, manufacture, compositions of matter, means, methods, or steps, presently existing or later to be developed that perform substantially the same function or achieve substantially the same result as the corresponding embodiments described herein can be utilized according to the present examples. Accordingly, the appended claims are intended to include within their scope such processes, machines, manufacture, compositions of matter, means, methods, or steps.

The invention claimed is:

1. A method comprising:

receiving, at a processor of a mobile device, a plurality of images from a camera, at least one image of the plurality of images including an object and at least one image of the plurality of images including an identifier associated with the object;
displaying a camera video stream based on the plurality of images;
sending identifier data from the mobile device to a server, the identifier data based on the identifier;
receiving video content at the mobile device from the server, the video content corresponding to the identifier data;
displaying three dimensional (3D) augmented reality content in the camera video stream; and
displaying the video content on at least a portion of the 3D augmented reality content in the camera video stream, the video content associated with the object.

2. The method of claim 1, wherein the object includes a package having one or more items, the package delivered to a user associated with the mobile device, and wherein presentation of the camera video stream including the 3D augmented reality content and the video content is associated with a multimedia message.

26

3. The method of claim 1, further comprising:
receiving, at the mobile device, an application;
storing the application at a memory of the mobile device;
and
accessing the application.

4. The method of claim 1, further comprising:
detecting, by the mobile device, the identifier included in a first image of the plurality of images,
extracting, by the mobile device, the identifier data from the first image; and
transmitting, by the mobile device, the identifier data to the server.

5. The method of claim 4, wherein:
the video content corresponds to the identifier and is associated with a sender of the object, and
the video content comprises audio/visual content.

6. The method of claim 4, further comprising:
accessing, by the processor, the camera of the mobile device; and
initiating, by the processor, a prompt to capture the first image of the identifier,
wherein the identifier comprises a marker coupled to the object.

7. The method of claim 4, wherein the video content comprises personalized video data submitted to the server by a third party.

8. The method of claim 1, further comprising:
receiving, at the processor, a second image from the camera;
detecting, by the processor based on the second image, the object or a marker coupled to the object;
tracking, by the processor, at least a portion of the marker in the plurality of images;
determining position information associated with the marker in one or more images of the plurality of images; and
displaying the 3D augmented reality content within the camera video stream based on the position information.

9. The method of claim 8, further comprising:
receiving, by the processor, placement data associated with the 3D augmented reality content; and
determining, by the processor based on the position information and the placement data, a position of the video content in relation to the 3D augmented reality content, one or more presentation characteristics of the video content, or a combination thereof.

10. The method of claim 4, further comprising:
receiving text data, image data, or both at the mobile device from the server based on the identifier;
displaying the text data, the image data, or both in the camera video stream; and
arranging the text data, the image data, or both based on the 3D augmented reality content.

11. The method of claim 1, further comprising:
sending, from the mobile device to the server, a notification associated with a completion of display of the 3D augmented reality content, the video content, or both, at the mobile device.

12. The method of claim 4, further comprising:
initiating a prompt to send a message based on a completion of the 3D augmented reality content, the video content, or both;
receiving an input to send the message; and
sending the message to the server, a device associated with a sender of the object, or both.

27

13. The method of claim 1, further comprising:
 establishing communication with the server;
 initiating, via the server, an order for delivery of an item
 to a recipient;
 generating order request information; and
 communicating the order request information to the
 server.

14. The method claim 13, wherein:
 generating the order request information comprises:
 selecting the item; and
 selecting an option to deliver a multimedia message to
 the recipient; and
 selecting the option to deliver the multimedia message
 comprises:
 selecting order 3D augmented reality content;
 providing order video content;
 providing a text content;
 providing an image; or
 a combination thereof.

15. The method of claim 14, further comprising:
 receiving confirmation of delivery of the item to the
 recipient; and
 receiving a notification that the multimedia message has
 been viewed.

16. The method of claim 1, wherein the identifier data
 enables selection at the server of the video content for
 sending to the mobile device from other video content
 corresponding to other identifier data.

17. The method of claim 1, further comprising:
 receiving placement data associated with a relative posi-
 tion of the video content; and
 determining a position of the video content within the
 camera video stream based on the placement data and
 a location of the 3D augmented reality content within
 the camera video stream.

18. The method of claim 1, further comprising:
 defining a placement boundary on a first 3D object of the
 3D augmented reality content based on a position of the
 3D augmented reality content in the camera video
 stream,
 wherein displaying the video content comprises display-
 ing the video content within the placement boundary in
 the camera video stream.

19. A device comprising:
 a processor; and
 a memory storing one or more instructions that, when
 executed by the processor, cause the processor to:
 receive a plurality of images from a camera, at least one
 image of the plurality of images including an object
 and at least one image of the plurality of images
 including an identifier associated with the object;
 display a camera video stream based on the plurality of
 images;
 send identifier data to a server, the identifier data based
 on the identifier;

28

receive video content from the server, the video content
 corresponding to the identifier data;
 display three dimensional (3D) augmented reality con-
 tent in the camera video stream; and

display the video content on at least a portion of the 3D
 augmented reality content in the camera video
 stream, the video content associated with the object.

20. The device of claim 19, further comprising:
 a display coupled to the processor; or
 the camera coupled to the processor; or
 a combination thereof.

21. The device of claim 19, wherein the one or more
 instructions are included in an application that is stored at
 the memory.

22. The device of claim 19, wherein the memory is further
 configured to store the 3D augmented reality content, the
 video content, or a combination thereof, and wherein the one
 or more instructions, when executed by the processor, fur-
 ther cause the processor to initiate storage at the memory of
 multimedia content presented via the display, the multime-
 dia content associated with the camera video stream, the 3D
 augmented reality content, the video content, or a combi-
 nation thereof.

23. The device of claim 19, further comprising a network
 interface coupled to the processor, wherein the network
 interface comprises:

a transmitter coupled to the processor, the transmitter
 configured to transmit one or more wireless signals;
 a receiver coupled to the processor, the receiver config-
 ured to receive one or more wireless signals; or
 a combination thereof.

24. A non-transitory computer-readable storage medium
 storing instructions that, when executed by one or more
 processors, cause the one or more processors to perform
 operations comprising:

receiving, at a processor of a mobile device, a plurality of
 images from a camera, at least one image of the
 plurality of images including an object and at least one
 image of the plurality of images including an identifier
 associated with the object;

displaying a camera video stream based on the plurality of
 images;

sending identifier data from the mobile device to a server,
 the identifier data based on the identifier;

receiving video content at the mobile device from the
 server, the video content corresponding to the identifier
 data;

displaying three dimensional (3D) augmented reality con-
 tent in the camera video stream; and

displaying the video content on at least a portion of the 3D
 augmented reality content in the camera video stream,
 the video content associated with the object.

* * * * *